

## PRECAST MARK 4 TYPE TOILET WITH CONCRETE ROOF

[DOWNLOAD OUR BROCHURE](#)

[mark 3](#) | [mark 4 - steel roof](#) | [mark 4 - concrete roof](#) | [mark 4 - disabled](#) | [mark 8](#) | [bottom structure](#)

Our precast Ventilation Improved Pit (VIP) toilets are specifically designed to create better sanitation for all, guidelines laid out by government initiatives. This system offers improved air circulation which limits the opportunity for disease. Internal dimensions of 890mm wide by 1100mm long by 1950mm high.

**Concrete Base Slab** Consists of main slab to accommodate top structure and filler slab along side.

Main Slab	: 1.5m x 1.0m x 0.050mm
Filler Panel Slab	: 1.5m x 0.5m x 0.050mm
Mass of main slab	: 176kg
Mass of filler slab	: 86kg
Reinforcing	: 311 mesh

4 x galvanized studs cast and recessed into base on main slab.

**Side Panel**

- 1.1m long x 605mm high x 35mm thick.
- Mass 57kg
- 4mm wire with fibres

**Back Panel**

- 850mm long x 605mm high x 35mm thick
- Mass 40kg
- 4mm wire with fibres

**Top Frame**

- 1.6m galvanized channel posts with 2.5mm thick base plate
- 2 x front posts 2 x rear posts (corner)
- IBR roof 0.58mm galvanized steel welded to 25 x 25mm angle iron frame
- Roof and posts fixed with 4 x 8mm cup square bolts/nuts
- Independent steel swivel door 1.6m high x 870mm wide
- Mass 24kg

All concrete is manufactured to 35 MPA

